



## FieldServer LonWorks® Gateway FS-B4011-01

*A 10-serial, 2-Ethernet port, 1-LonWorks® protocol translator gateway enables data transfer between serial, Ethernet and LonWorks® protocols. An extensive library of drivers provides easy interoperability between a variety of devices used in building automation, HVAC, fire and process control industries.*

### Serial – Ethernet - LonWorks®

The FieldServer is a protocol translator/gateway which enables devices using one protocol to communicate with devices using another protocol. An example is a fire alarm panel using a proprietary manufacturer's protocol needing to supply alarm information to a building automation system using LonWorks. In a single, comprehensive package the FieldServer provides the hardware and software necessary for this translation. The FS-B4011 Series includes eight RS-232 ports, two RS-485 ports, two Ethernet (10BaseT) ports, and one LonWorks port to interface to the devices. All the necessary software and instructions for configuration are supplied with the FieldServer. FieldServer Technologies also offers fee based configuration services. FieldServers are available for various fieldbuses.

### Specifications

#### Field Connections

- **Ethernet Ports**
  - Qty 2 - 10BaseT RJ45 connector
- **Serial Ports**
  - Qty 8 RS-232 ports, RJ45 connector
  - Qty 2 RS-485 ports, terminal connector
  - Up to 115K baud
- **LonWorks Port**
  - FTT-10 twisted pair
  - 4095 Network variable capability
  - UNVT or SNVT variable support
  - Explicit (Polled Mode) or Implicit (Bound Mode) Addressing
- **Drivers**
  - Drivers available for a wide range of Ethernet and serial protocols

#### Host PC Connections (for Configuration)

- Ethernet 10BaseT
- RS-232 or RS-485

#### LED Indicators

- Power, Run, System Error, Configuration Error
- Port connections – Tx/Rx communication activity

#### Other

- Service Pin for LonWorks Node identification
- Configuration utility
- Diagnostic utility
- System integration services available

#### Power Requirements

- 120/220 VAC, 50/60 Hz, 1 amp

#### Environment

- Operating temperature: 0-60°C (32-144°F)
- Relative humidity: 10-95% RH non-condensing

#### Physical Dimensions

- 7.5 x 12.0 x 2.2 in. (WxDxH)  
(19.1 x 30.5 x 5.6 cm)
- 5.0 lbs (3.0 Kg)

#### Mounting Options

- Desktop
- Wall
- 19-inch rack mount

#### Approvals

- UL 1950
- CE Marked

